

# Flex Classic Mirror

## CUTTING

PLOTTER	SETTINGS	
<b>Summacut D60-R</b>	<b>SPEED</b>	50 mms
	<b>PRESSURE</b>	90g - 100g
	<b>AUTOLOAD</b>	On
	<b>KNIFE OFFSET</b>	45
	<b>OVERCUT</b>	1mm
	<b>OPTICUT</b>	Off
	<b>FLEXCUT</b>	Accurate
	<b>CONCANTENATION</b>	2

**Instructions** Cut the material with your design in MIRROR image.  
Once cut, weed the excess material, taking particular care with any small details.  
Flex Classic Mirror does not adhere to fabric that has a treated surface, it is advisable to test on the garment prior to application if you are not sure.

## APPLICATION

HEAT PRESS	SETTINGS	
<b>Transmatic TMH 28</b>	<b>PRESSURE</b>	Medium
	<b>TEMPERATURE</b>	150° - 160° C
	<b>TIME</b>	12 Seconds

**Instructions** Remove the polyester carrier film once the garment is cool.

## WASHING INSTRUCTIONS

We recommend washing the garment inside out.

We recommend washing the garment at 40° C (Product has been tested up to 60° C).

The product can also withstand standard household detergents.

## FABRIC

Cotton & Polyester